



Metal Work Mechatronics concise





Metal Work Mechatronics: know how e sinergia al vostro servizio. Metal Work Mechatronics: know-how and synergy at your service.



Cilindri elettrici, serie Elektro ISO 15552, diametri da 32 a 100 mm; serie Elektro ISO 15552 EK diametro 32 mm

Electric cylinder, Elektro ISO 15552 Series, diameters from 32 to 100 mm; Elektro ISO 15552 EK Series, diameter 32



Cilindri elettrici, serie Elektro Round DC, diametro 32 mm

Electric cylinders, Round DC Elektro Series, diameter 32



Cilindri elettrici, serie Elektro SSC, diametro 32 mm

Electric cylinder, Elektro SSC Series, diameter 32 mm



Assi elettrici senza stelo a cinghia, serie Elektro Shak, con motore BRUSHLESS o PASSO-PASSO

Belt-drive rodless electric axis, Shak Elektro Series, with BRUSHLESS or STEPPING motor



Assi elettrici cantilever, senza stelo a cinghia, con motore posizionato sul carrello, serie Elektro VBK e serie Elektro SVAK.

Cantilever electric axis, belt-drive rodless, with motor placed on the carriage, Elektro VBK series and Elektro SVAK series.



Portale con due assi a cinghia paralleli sormontati da un asse trasversale, serie Elektro Shak Gantry

Two parallel belt-drive axis surmounted by a transversal axis, Shak Gantry Elektro Series



Assi elettrici senza stelo a vite, serie Elektro SK, e assi elettrici senza stelo a cinghia dentata, serie Elektro BK

Screw rodless electric axis, Elektro SK Series, and rodless electric axis with toothed belt, Elektro BK Series



Dispositivi di controllo, programmatore e.motion, azionamento programmabile e.drive, ed azionamento e.direct

Control devices, e.motion programmer, e.drive programmable drive, and e.direct drive



Unità di guida, slitte piatte e slitte di precisione, serie S10, S11, S12, S13 e S14

Guide units, flat slides and precision slides, Series S10, S11, S12, S13 and S14



Prodotti customizzati in alluminio, in acciaio legato e in acciaio inox, studiati in collaborazione con il cliente

Customized products made of aluminum, either alloy steel and stainless steel, studied in cooperation with the customer according to specific requirements



Ampia gamma di pinze pneumatiche a 2 e 3 griffe

Wide range of 2 and 3 jaws pneumatic grippers



Attuatori rotanti robusti e potenti per coppie fino a 120 Nm, diametri da 12 a 100 mm

Stout and powerful rotary actuators for torques up to 120 Nm, diameters from 12 to 100 mm



Sistema elettro-pneumatico, serie EB80, da 3 a 128 elettropiloti

Electro-pneumatic system, EB80 Series, from 3 to 128 solenoid pilots

